

Nylon Hoses / Nylonschläuche



Order No Bestellnr.	Internal Dia. Innendurchmesser		Outside Dia Außendurchmesser mm	Max. Working Pressure at 20° C Max. Betriebsdruck 20° C Bar	Bursting Pressure at 20° C Berstdruck 20° C Bar	Length Länge m.	Colour Farbe	
	mm	Inch.					Neutral	Transparent
NLH - 06	6	1/4	11.5	7	21	100	Neutral	Transparent
NLH - 06B	6	1/4	11.5	7	21	100	Blue	Bleu
NLH - 06R	6	1/4	11.5	7	21	100	Red	Rouge
NLH - 08	8	5/16	13.8	7	21	100	Neutral	Transparent
NLH - 08B	8	5/16	13.8	7	21	100	Blue	Bleu
NLH - 08R	8	5/16	13.8	7	21	100	Red	Rouge
NLH - 10	9.5	3/8	15	7	21	100	Neutral	Transparent
NLH - 10B	9.5	3/8	15	7	21	100	Blue	Bleu
NLH - 10R	9.5	3/8	15	7	21	100	Red	Rouge
NLH - 13	12.7	1/2	18	7	21	100	Neutral	Transparent
NLH - 13B	12.7	1/2	18	7	21	100	Blue	Bleu
NLH - 13R	12.7	1/2	18	7	21	100	Red	Rouge
NLH - 16	16	5/8	23	7	21	100	Neutral	Transparent
NLH - 19	19	3/4	26.4	7	21	100	Neutral	Transparent
NLH - 23	25	1	33.4	7	21	100	Neutral	Transparent

Structure

PVC hose with polyester reinforcement kink resistant and flexible. Also available in food industry

Structure

PVC Schläuche mit Polyesterbewehrung, ist knickbeständig und biegsam. Anwendbar in Lebensmittelindustrie.

Working Temperature Range

Static conditions : -20° C to + 65° C
Dynamic conditions : - 5° C to + 50° C

Température d'utilisation

en Statique : -20° C to + 65° C
en Dynamique : - 5° C to + 50° C